

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of the claims in the application:

Listing of Claims:

1-27. (Cancelled)

28. (Currently amended) A method, comprising:

sensing a directional movement with a first movement sensor coupled to a bottom face of a lower section of a computer system having an upper section parallel to the lower section;

sensing an angular position of the computer system with a second movement sensor coupled to the bottom face of the lower section of the computer system;

adjusting information displayed on a display of the computer system, the information displayed correlated to the directional movement and angular position, the display being part of the upper section;

sensing external pressure on a frame of the display of the upper section, the external pressure to move a plane of the upper section; and

translating the external pressure on the upper section to a mouse click action associated with an operation corresponding to the movement of the plane of the upper section relative to the lower section of the computer system.

29. (Currently amended) The method of claim 28, wherein the first and second movement sensor is an optical sensor or a mechanical sensor.

30. (Currently amended) The method of claim 28, wherein the first movement sensor is a trackball.

31. (Previously Presented) The method of claim 28, further comprising:

correlating the directional movement to a cursor movement on the display of the computer system.

32. (cancelled)

33. (Currently amended) A method, comprising:

sensing an external pressure on a frame of a display in an upper section of a computer system, the external pressure to move a plane of the upper section of the computer system, ~~the upper section having a display of the computer system~~; and

translating the external pressure on the upper section to a mouse clicking action associated with an operation corresponding to the movement of the plane of the upper section relative to the lower section of the computer system.

34. (Currently amended) The method of claim 33, wherein the external pressure is applied towards a movement sensor coupled to the lower section of the computer system.

35. (Previously Presented) The method of claim 33 further comprising:

translating the external pressure to a first mouse clicking action when the external pressure is applied to a first portion of the upper section so that the plane of the upper section intersects the lower section;

translating the external pressure to a second mouse clicking action when the external pressure is applied to a second portion of the upper section so that the plane of the upper section intersects the lower section; and

translating the external pressure to a third mouse clicking action when the external pressure is applied to a central region of the upper section so that the entire plane of the upper section moves towards the lower section.

36. (cancelled).

37. (Currently amended) A computer-readable storage medium having stored thereon sequences of instructions which are executable by a computer system, and which, when executed by the computer system, cause the computer system to perform a method, comprising:

sensing a directional movement with a first movement sensor coupled to a bottom face of a lower section of a computer system having an upper section parallel to the lower section;

sensing an angular position of the computer system with a second movement sensor coupled to the bottom face of the lower section of the computer system;

adjusting information displayed on a display of the computer system, the information displayed correlated to the directional movement and angular position, the display being part of the upper section;

sensing external pressure on a frame of the display of the upper section, the external pressure to move a plane of the upper section; and

translating the external pressure on the to a mouse click action associated with an operation corresponding to the movement of the plane of the upper section relative to the lower section of the computer system.

38. (Currently amended) A computer-readable storage medium having stored thereon sequences of instructions which are executable by a computer system, and which, when executed by the computer system, cause the computer system to perform a method, comprising:

sensing an external pressure on a frame of a display in an upper section of a computer system, the external pressure to move a plane of the upper section of the computer system, ~~the upper section having a display of the computer system;~~ and

translating the external pressure on the upper section to a mouse clicking action associated with an operation corresponding to the movement of the plane of the upper section relative to the lower section of the computer system.

39. (Previously Presented) The method of claim 28, further comprising:

translating the external pressure to a first mouse clicking action when the external pressure is applied to a first portion of the upper section so that the plane of the upper section intersects the lower section;

translating the external pressure to a second mouse clicking action when the external pressure is applied to a second portion of the upper section so that the plane of the upper section intersects the lower section; and

translating the external pressure to a third mouse clicking action when the external pressure is applied to a central region of the upper section so that the entire plane of the upper section moves towards the lower section.